

## Specification Sheet: Refrigerated Trailer



Refrigerated Trailer Specifications	
Delivery Mechanism	Tractor (Semi-truck)
Color	Variable; Unmarked required, white preferred
Length	Variable; Should not exceed 53'
Width	Variable; Should not exceed 8'5"
Overall Height	Variable; Should not exceed 13' 6"
Loading Height	Variable; Typically between 48" to 55"
Floor Type	Extruded metal or flat polymer ("grocery floor")
Temperature	37 degrees Fahrenheit
Power Source	<ul style="list-style-type: none"> <li>▪ Diesel fuel</li> <li>▪ Electric (230 volts, 3-phase, 50 amps circuit, CS plug style)</li> </ul>
Fueling	Generally every 2 – 3 days
Maintenance:	Every 6 months or as needed
Shelving:	<ul style="list-style-type: none"> <li>▪ Unit will not come with shelves</li> <li>▪ Shelves can be added as necessary and available</li> </ul>
Security	<ul style="list-style-type: none"> <li>▪ Rear door: Secured with high-secure hardened steel lock</li> <li>▪ Kingpin: Appropriate kingpin lock for trailer type</li> </ul>
Loading	Direct via loading dock or lift gate
Capacity	Approximately 9 – 44
Refrigeration	<ul style="list-style-type: none"> <li>▪ Must be requested – does not come standard</li> <li>▪ Must maintain 37 F</li> </ul>

**Note:** Most refrigerated trailers are powered with diesel fuel. Refueling requirements will vary, but generally trailers will need to be refueled every two to three days. Some refrigerated trailers may come with an electric standby mode on the refrigeration unit which will allow it to run solely on electrical power. Refrigeration units can also be plugged into the main facility's electrical grid without significant alterations. Internal temperatures should be strictly monitored to ensure a constant 37° F temperature. Maintenance needs and requirements should be noted and communicated to the HCF Morgue Manager.

## Specification Sheet: Refrigerated CONEX Unit



Refrigerated CONEX Unit Specifications	
Delivery Mechanism	Flatbed or roll-off tractor trailer; Heavy duty forklift or crane
Color	Variable; Unmarked required
Length	20' or 40'
Width	8'
Overall Height	8'6"
Loading Height	Level
Floor type	Metal/steel
Temperature	37 degrees Fahrenheit
Power Source	<ul style="list-style-type: none"> <li>▪ Diesel fuel</li> <li>▪ Electric (380/460 volts, 3-phase, 50/60 Hz, 50 amp power supply)</li> </ul>
Fueling	Generally every 2 – 3 days
Maintenance	Every 6 months or as needed
Shelving	<ul style="list-style-type: none"> <li>▪ Unit will not come with shelves</li> <li>▪ Shelves can be added as necessary and available</li> </ul>
Security	Rear doors: Secured with high-secure hardened steel lock
Loading	Direct from ground level
Capacity	Approximately 16-29
Refrigeration	Must be requested – does not come standard Must maintain 37 F